

Single Lane Flap Barrier Turnstile Gate

TFB260 PRO



Its full Body stainless steel casework ensures long-lasting durability. High-quality electrical components. Barriers retract automatically during emergencies. Smooth finish. No exposed screws. Ergonomic design makes cards and fingerprints. authentication fast & simple for users. TFB260 PRO series ships already integrated with our customers' preference for either card or fingerprint access control reader. AIRCOM provides true plug & play turnstiles with the lowest possible total cost of ownership in the industry

SPECIFICATION

- Power Requirements: AC 100 ~ 120V / 200 ~ 240V, 50 / 60Hz
- Working Temperature: -28°C ~ 60°C
- Working Humidity: 5% ~ 80%
- Working Environment: Indoor/outdoor (if sheltered)
- Speed of Throughput: Maximum 30 / minute
- Lane Width (mm): 600
- Dimension (L*W*H): 4* 1* 3(ft.)
- Dimension with Packing: (L*W*H)1510 * 420 * 1230 (mm)
- LED Indicator: Support
- Cabinet Material: SUS304 Stainless Steel
- Lid Material: SUS304 Stainless Steel + Acrylic
- Barrier Material: Acrylic (optional: tempered glass)
- Barrier Movement: Retracting
- Emergency Mode: Support
- MCBF: 2million