LCD HDMI Matrix AIR_MTX_16x16

Picture

Key Features

- Support 4K · 3840x2160@30Hz Input
- Seamless Switching
- Full Corlor LCD Screen Display
- Support Web Upper-Computer Control
- 16 HDMI Video Input, 16 HDMI Video Output
- Support HDCP
- One Key Black Screen
- Built-in 11 Testing Patterns
- Multi-Screen Manage
- Matrix Mode

System Topology

Parameter

Port Specifications	
HDMI Port 16*HDMI Input 16*HDMI Output	Signal Standard: HDMI1.4 Backward Compatible Resolution: VESA Standard, ≤3840×2160p@30Hz Interface Type: HDMI-A Socket
Net Ethernet Port	Interface Type: RJ45; Web Version Upper PC Control Can Be Achieved By Connecting The Computer Through Ethernet Cable;
USB Port	USB-B, Can Upgraded The Device Programs Through USB Disk;
RS232 Serial Port	By The Upper-PC Protocol To Control, RS232 Has Loop-out Function, Which Can Be Cascaded And Controlled Multiple Devices;
Extended Port	EXT、ANT Extended Interface, Not Enabled;
Performance	
Switching Method	Seamless Switching, Audio&Video Sync Output;
Device Language	Standard Version Is English, Other Languages Require Need Remarks;
General Specifications	
Power Supply	Mean Well Brand·Built-in, 100～240V AC, 50～60Hz;
Temperature	Storage : T: -40℃ ~ +80℃、 H: 10% ~ 90%, Non-condensing; Working: T: 0℃ ~ +60℃、 H: 10% ~ 90%, Non-condensing;
Machine Size	485mm (L) x 375mm (W) x 77mm (H)
Packing Size	535mm (L) x 435mm (W) x 120mm (H)
Product Weight	Gross Weight : 5.0Kg ;
Package Weight	Volume Weight: 6.0Kg ;
Warranty	1 Year; Note: All Rated Voltages Are On Average ±10%;
Packing List	
Standard	Power Cable * 1, Certificate * 1;Warranty Card * 1;

Model	Description	P/N
AIR_MTX_16x16	Standard Model	PN202411016

AIRCOM Digital Electronics Inc.

Aircom Digital www.aircomdigital.com sales@aircomdigital.com

Add: 12015 Panthers Ridge Drive, Germantown. MD20876-USA